# RD-12/22-100A

Automatic High-Speed Paper Cup Machine 全自动高速纸杯机

Http://www.nan-da.com Http://zhejiang-ruida.en.alibaba.com E-mail:nanda@nan-da.com

### 专业/高效/可靠 Professional / Efficient / Reliable

### 简介 DESCRIPTION:

本、是制作抵怀的最优政策。

RD-12/22-100A high speed paper cup forming machine com with two tumplate, open intermittent indexing cam mechanis and gear transmission, longitudinal axis structures. The winnerhead policy automatic lubrication system, which makes is done by Switzerland Leister Heater to ensure side seal istability, bottom sealing by Switzerland Leister for device. C top curling has two steps, rotary curling and healing figuration which makes the curling more stable and better appearance. T machine comes with PLC control system, sensor/faiture detection and the curling more stable and better appearance is machine comes with PLC control system, sensor/faiture detection control of the curling more stable and better appearance. The machine comes with PLC control system, sensor/faiture detection control of the curling more stable and better appearance. The machine can finish the whole process in cluid paper feeding, side sealing, cup bottom punching &feedin heating, knurling, cup-lop curling, cup Slacker, It is the bid sealing the page of the page of



纸杯规格(Cups Specifications)	4-16盎司(Ounce) 16-22盎司(Ounce
纸杯材料(Cups material)	单双面PE 淋膜纸(任意一种都可以 Single or double PE Coated Paper
纸张规格(Paper Specifications)	190-380g/m <sup>2</sup>
生产速度(Speed)	120-160 pcs/min
电源(Electricity Supply)	380V/220V 50Hz
总功率(General Power)	10Kw
气源(Gas source)	0.4m³/min
重量(Weight)	3000Kg
包装尺寸(Packing Dimensions)	2750x1720x1800mm





(€ · RUIDA MACHINERY 03-04

## RD-12/22-100B

PLC Control Paper Cup/Bowl Forming Machine With Automatic Lubrication System B型中速纸杯/碗成型机

专业/高效/可靠 Professional / Efficient / Reliable







### 士車技术条数 Tooksical Data

机型 Model	纸杯 Paper cup	纸碗Paperbowl
规格Specification	2.5-22 OZ	24-40 OZ
纸杯材料Paper material	190-500g/m <sup>2</sup>	190-500g/m <sup>2</sup>
生产能力Speed	80-100 pcs/min	80-90pcs/min
电源总功率Total power	380V 50Hz 10Kw	380V 50Hz 12Kw
气源Air consumption	0.4m³/min	0.5m³/min
重量Weight	3500kg	4000 Kg
包装尺寸Packing Dimensions	2720x1660x1900 mm	2900*1860*2000mm

